

Trimline Acoustical & Tackable Panel Suggested Architectural Specifications

Acoustical & Tackable Panels shall be custom Trimline Acoustical & Tackable Panels from AcousticalPanelMfg.com / WIUSA.com, div. of Wallcovering Industries, Inc., PO Box 571249, Dallas, TX 75357, Contact 800-527-9014 or 214-327-4100, Email: sales@acousticalpanelmfg.com or sales@wiusa.com. ' Made in USA '

Prefinished factory assembled Trimline panels shall consist of a molded 1/2" thick core of 10 lb. density fiberglass.

Panel components shall have a Class 'A' Flame Spread ratings of 25 or less as determined by ASTM-E-84 Tunnel Test.

Panels shall have, depending on covering choice, a nominal NRC rating with range of .55 to .80, when tested in accordance with ASTM-C-423-81, based on test mounting 'A'.

In addition, photocopies of the test results from an accredited testing laboratory shall be submitted to the specifier / owner to substantiate the sound reduction frequencies conform to the criteria as outlined in the specification.

The covering specified shall be Pattern _____, Colorway _____. The fabric covering shall be bonded directly to the panel surface or stretched, wrapped and adhered to the sides and back of the panel. Fabrication procedures will ensure an aesthetically pleasing surface finish.

The appropriate hardware for mounting, if any, as determined most suitable by the manufacturer shall be either adhesive, hook & loop or L-Clips as selected by the specifier.

Shipment: To avoid damage in transit, panels must be packaged in 275 lb. test double corrugated cardboard carton, total weight not to exceed 150 pounds.

Installation: The contractor shall furnish all labor, materials, services and equipment necessary for, and reasonably incidental to the installation of the panels as shown on drawings and as specified herein.

Warranty: All panel and baffle materials provided and installed within the original manufacturer's standards for installation shall be warranted for a period of one (1) year from date of sale against defects to material provided a climate controlled environment is maintained from panel installation through enduser use, and no evidence of panel abuse or water damage. Limited to specific panel replacement. No labor allowed. For additional information - Inquire.

For Quotation and Information call us USA 800.527.9014, or
Email: sales@acousticalpanelmfg.com or sales@wiusa.com.

‘ Making Walls Productive Since 1979 ‘

